

## Series ETC-366GX/LX Handheld PC

eTech Connect b.v. delivers a comprehensive product line of network-ready information appliances, enabling access to the Internet and Intranet, anytime, anywhere. The new *ETC-366xx* expands eTC's portfolio of innovative and practical solutions, targeting a wide range of applications, leveraging cost effective and manageable platforms.



### **THE PRODUCT**

The *ETC-366* features the integration of a bright 8.4" touch display over an efficient AMD Geode-powered electronics platform within a thin, light, yet robust, metal package. Versatility reflected in the hardware and software features makes the device applicable for deployment leveraging network access and custom software.



### **FEATURES**

- support for major embedded operating systems
- protective rubber jacket for ruggedized needs
- accessible yet securable interfaces for range of peripherals and accessories
- configurability for different storage and networking requirements
- multiple options for battery expansion
- display option for outdoor viewability

### **APPLICATIONS**

The *ETC-366xx*, finds applications in:

- **Server-based Computing, Education**
- **Control & Monitoring, Transportation**
- **Inventory & Warehousing, Service Industry**
- **Web-based Applications, Manufacturing**

and numerous *other* vertical markets.

A suite of customized accessories complements the *ETC-366xx* to meet numerous deployments needs.



## ET-366GX/LX Digital Tablet for High Performance

### SPECIFICATIONS

Display	8.4" (diag.) TFT LCD with Resistive Touch; Outdoor-Viewable option
Display Resolution	(SVGA)
Processor	<b>AMD:</b> Geode GX, Geode LX
Memory (flash)	64MB – 4GB
Memory (RAM)	256MB (GX); 512MB (LX)
Software Operating Systems	Windows CE (GX only); Windows XP Embedded; Windows XP Professional
Storage	Internal flash module; CompactFlash slot or HDD; USB
Enclosure	Magnesium-Aluminum alloy
Stylus	Yes
Desktop Cradle	Pass-through for Power and USB for Keyboard and Mouse
Protective Jacket	Adds drop protection
AC/DC adapter	Input: 90-240VAC Output: 12VDC, 3.5A
Power Cords	USA, EU, UK
Battery Packs (Lithium-Ion)	Internal (14W) <b>Optional:</b> External (28W, 0.5lb), and Tethered Pouch (72W, 1lb)
Network Interface (incl. WLAN)	PCMCIA or mini-PCI; USB; Bluetooth Built-in; CF Slot
Wireless WAN	PCMCIA
Input & Control Buttons	Four (4) Front buttons; One (1) Oval 4-Way; One Power (left edge); One "Trigger" (right edge)
Input/Output Ports	12V DC-in Jack; Microphone-In; Headset Jack; USB (1.1) Port
Dimensions (H x W x D)	7.9 x 9.6 x 0.8 (in) 200 x 240 x 18 (mm)
Base Weight	1.9 lbs (0.86 kg)
Regulatory	FCC Class B, CE, UL
Operating Temp.	0° – 40°C
Humidity	0% – 90%

### KEY ACCESSORIES



- Car mount cradle
- 1 off USB Port
  - 1 off LAN Port
  - VESA drilling
  - 12VDC



Charging device for external battery pack

Your Dealer:

*Specifications subject to change without prior notice.*

