

Series ETC-550 & 570 Display-Integrated Terminals

eTech Connect b.v. delivers a comprehensive product line of network-ready information appliances, enabling access to the Internet and Intranet, anytime, anywhere. The new *ETC-5xx* expands eTC's portfolio of innovative and practical solutions, targeting a wide range of applications, leveraging cost effective and manageable platforms.



THE PRODUCT

The WebETC-500 features the integration of the energy efficient, yet powerful AMD Geode LX800 processor "low power" technology into a most compact and robust enclosure. The space-saving package accommodates accessories and peripherals to address a range of applications. Designed for, 24 hours operation over many years. The software operating systems support server- and browser based computing in addition to local, embedded applications. The versatility in hardware and software makes the device compelling for numerous vertical deployments leveraging network access and custom software.

FEATURES

- support for major embedded operating systems and Windows XP
- integrates major thin-client/server computing protocols (Citrix ICA, MS RDP), terminal emulation suite; and web browsers
- amenable to comprehensive and easy remote device administration through ETC's server based Remote Manager Software
- configurability for thin-client/server computing; or local application shell
- spill-resistant display surface for usage in harsh environments, industrial type Flash memory base and hard drive for long operation
- comprehensive set of USB and I/O ports; interface and support for a wide range of peripherals and accessories
- VESA-mountable display panel system for flexibility in mounting and deployment.
- Options for robust 5-wire touch screen display and integrated 802.11 b/g wireless LAN adapter

APPLICATIONS

The WebETC-550 and 570, like other members in the ETC product family, finds application in a variety of industries, including:

- **Server-based Computing, Education**
- **Control & Monitoring, Transportation**
- **Inventory & Warehousing, Service Industry**
- **Web-based Applications, Manufacturing**
- **POS and KIOSK Integration**

and numerous *other* vertical markets.

A suite of customized accessories complements the ETC-5xx to meet numerous deployments needs.

WebETC-550 & 570 Display-Integrated Terminals

SPECIFICATIONS

Display Resolution	15" (WebET-C550) TFT LCD 17" (WebET-C570) TFT LCD 50.000 hours lamp life
Display Resolution	15": 1024x768 (XGA) 17": 1280x1024 (SXGA)
Processor	AMD: Geode LX800 Via Eden 1GHz
Memory (flash)	64MB – 8GB
Memory (RAM)	128MB – 1GB
Software Operating Systems	Windows CE; Windows XP Embedded; Windows XP Professional
Storage	Internal flash module; CompactFlash slot or HDD; External USB
Enclosure	ABS Platic
AC/DC adapter	Input: 90-240VAC Output: 12VDC, 1,2Amp.
Power Cords	USA, EU, UK
Network Interface	Mini-PCI; RJ45 Ethernet
Control Buttons	Five (5) Front Buttons
Input/Output Ports	18,5VDC Jack In; Microphone-In; Audio-Out Jack; 2 off USB2.0 Ports;
	1 off Parallel and 2 off RS232 10/100 Base T Ethernet PS/2 Keyboard and Mouse
Dimensions (H x W x D)	13.8 x 14 x 6.7 (in) 350 x 355 x 170 (mm)
Base Weight	8.8 lbs (4.0 kg)
Regulatory	FCC Class B, CE
Operating Temp.	0° – 40°C
Humidity	0% – 90% non-condensing



Standard Package and Accessories

- One (1) WebETC-550 or 570
- AC/DC Adapter with Power Cord
- Optional Full Size Keyboard and Mouse
- Documentation

Major Options

- Built-in wireless LAN
- 5-wire resistive touch screen
- Magnetic Stripe Reader
- Two (2) additional Serial RS232 Ports

Your Dealer:

Specifications subject to change without prior notice.

