

Series ETC-870 & 880 Panel PC

eTech Connect b.v. delivers a comprehensive product line of network-ready information appliances, enabling access to the Internet and Intranet, anytime, anywhere. The new *ETC-5xx* expands eTC's portfolio of innovative and practical solutions, targeting a wide range of applications, leveraging cost effective and manageable platforms.



THE PRODUCT

The WebETC-800 features the integration of vivid 7" (ETC-870) and 8.4" (ETC-880) displays with touch-screen and wired/wireless networking over an efficient, yet powerful AMD Geode GX533 platform. This is accomplished within an expandable and elegant space-saving packaging, amendable to enhancements for accommodating accessories and peripherals. The software operating systems support server- and browser based computing in addition to local, embedded applications. The versatility in hardware and software makes the device compelling for numerous vertical deployments leveraging network access and custom software.

FEATURES

- support for major embedded operating systems
- configurable for local application shell, or browser based computing, or thin-client/server computing
- integrates major thin-client protocols (Citrix ICA, MS RDP) terminal emulation suite, and web browsers
- amenable to comprehensive and easy remote device administration through ETC's server based Remote Management Software
- responsive touch-screen display
- USB Ports for peripherals and accessories
- Choice of power input for optimal deployment
- Comprehensive set of metal adaptors for flexibility in mounting and installation

APPLICATIONS

The WebETC-800, like other members in the ETC product family, finds application in a variety of industries, including:

- **Server-based Computing, Education**
- **Control & Monitoring, Transportation**
- **Inventory & Warehousing, Service Industry**
- **Web-based Applications, Manufacturing**
- **POS and KIOSK Integration**

and numerous *other* vertical markets.

Series WebETC-870 & 880 Panel PC

SPECIFICATIONS

Display Resolution	7" (WebETC-870) TFT LCD 8.4" (WebETC-880) TFT LCD
Display Resolution	800x600 (WebETC-870) 800x480 (WebETC-880)
Processor	AMD: Geode GX533
Memory (flash)	From 32MBB
Memory (RAM)	From 128MB
Software Operating Systems	Windows CE5.0, Windows XP Embedded;
Storage	Internal flash; External USB
Display	ABS Plastic
AC/DC adapter	Input: 90-240VAC Output: 12VDC, 3.5Amp..
Power Cords	USA, EU, UK
Network Interface	Mini-PCI; RJ45 Ethernet
Control Buttons	Four (4) Front Buttons
Input/Output Ports	12VDC Jack In; Microphone-In; Audio-Out Jack; 2 off USB2.0 Ports;
Wall Cut-outs	WebETC-870: 5.8 x 7.9" 147 x 200mm WebETC-880 7.6 x 9.5" 193 x 241mm
Bezel Outline & Thickness	WebETC-870 159 x 228 x 12mm WebETC-880 204 x 271 x 12mm
Base Weight	0.95 (870) 1.25 (880)
Regulatory	FCC Class B, CE
Operating Temp.	0° – 40°C
Humidity	0% – 90% non-condensing



Standard Package and Accessories

- One (1) WebETC-870 or 880
- AC/DC Adapter with Power Cord
- Phoenix Power Connector, Mounting Screws
- Metal Parts: Back-box, Grips, AC/DC bracket and Wing
- Documentation

Major Options

- Built-in wireless LAN
- AC/D C adaptor fot extended range power range
- Screen protectors

Your Dealer:

Specifications subject to change without prior notice.

